

# J32L637 32" LCD HDTV Commercial Monitor-Receiver







ClonePro<sup>™</sup> Programming



nan

HDTV/QAM Digital Tuner



Internal Power Supply with Safety Plug



Digital Serial Communications Interface

For more information, call 1.800.333.7221.

## J32L637 LCD HDTV



#### **Picture Technology**

Tuner Category Display Type Screen Size Display Aspect Ratio Display Resolution Brightness (cd/m2) Contrast Ratio Viewing Angle Horizontal/Vertical Response Time

LCD TFT LCD 32" 16 x 9 1366 x 768 550 1000 : 1 176/176 8 ms

ATSC/NTSC/QAM

## Sound Technology

 Broadcast Stereo Sound

 SAP (secondary audio program) where available

 Audio Power front speakers
 8 watts / channel x 2

 Headphone Adjustments

## **Commercial Features**

NTSC/ATSC/QAM Tuner for a wide range of options using off-air, satellite/cable or internally generated program signals.

**Channel-Guide with One-Button Access** for an on-screen listing of all available channels and their identification labels.

8-Character Channel Labeling allows for on-screen display of both network affiliation and channel number.

User Remote with TV1/TV2/TV3 Capability allows simultaneous control of multiple monitors in the same room.

ENERGY STAR\* Qualification saves energy costs.

Power Provisions for Third-Party Modules eliminate the need for walltransformers, wiring snarls and "set-top" boxes.

Digital Serial Communications Interface (DSCI) allows third-party interactive systems to monitor and control television with optimal performance and efficiency.

**Configuration Menus with Non-Volatile Memory** for site-specific specifications and limitations on how televisions can be operated and retained, even when power is lost.

Selectable Weak Signal Muting mutes audio, blanks video and provides an on-screen message if signal is weak or lost.

Selectable Clock and Scheduler with automatic time set allows TV signal to automatically set time (where available); scheduled turn on/off events can be one-time or recurring.

Volume Limiter and Initial Volume establish maximum and consistent initial volume settings each time television is turned on.

Selectable Automatic Turn-Off permits television to turn off automatically after a period of inactivity.

**IR and Wired Cloning Capabilities** allow rapid duplication of configuration information between televisions for ease of installation and maintenance.

©2006 TTE Technology, Inc.

Commercial Sales and Distribution • MS INH605 101 West 103rd Street • Indianapolis, Indiana 46290-1024

www.rca.com/rcacommercial • Phone: 1-800-333-7221

Side Access A/V Jacks offer convenient connection of external audio or video components.

Front Panel Lockout prevents tampering.

TTE

Commercial Cabinet with Mountable Stand provides integral mounting ability.

Software Upgrade Port to upgrade firmware in the field.

#### **Specifications**

Rea

Sid

Inputs Rear:	RF Input (ATSC/NTSC) • Composite Video Input • Audio Input for Composite/S-Vid • Dsub15 VGA • Audio input for RGB • Component Video Input (YCrCb/YPrPb) • Audio Input for Component Video • DVI – HDMI <sup>™</sup> • VGA Audio • Audio input for DVI –HDMI <sup>™</sup> (Menu Select) • DSCI Jack • I2C Connector • Software Upgrade
Inputs Side:	Composite Video Input • S-Video Input • Audio input for Composite
Outputs Rear:	Video Output • Audio Outputs
Outputs Side: ar	Headphone Jack
VGA VGA PUC	TO CONTROL ANTENNA V L R ANTENNA O O O O
COMPONENT IN 2 Cr Pb/Cb Y L R R O O O O O	UCUCIÓN L VIDEO OUT ANTENNA O O O O O O O O O O O O O O O O O O O
de	_
AUDIO IN VIDEO R L IN S-VIDEO HEADPH	

Internal power supply 3-prong grounded safety plug
120VAC (+/-)10%, 60Hz
Stand-by: less than 1 watt (ENERGY STAR Qualified)
Construction: high-impact flame-retardant polystyrene Finish: black Dimensions: 21.3"H, 36.1"W, 4.5"D Dimensions with stand: 23.6"H, 36.1"W, 9.4"D VESA mounting compatible: 400 x 200 hole pattern
Product 57.3 lbs./Shipping 65.4 lbs.
UL Commercial Listing
1 year parts and labor

This television receiver provides display of television closed-captioning in accordance with §15.119 of the FCC rules. This television does not support color attributes of television closed-captioning.

#### **Optional Accessories**

#### ClonePRO<sup>™</sup> Remote (CBX203)

This unique accessory significantly reduces installation and programming time, allowing you to program one television and then transfer the same data to all similar sets in just seconds. The more RCA televisions you install, the more efficiency you gain.

#### Master Remote (R130K2)

The RCA Master Remote maintains control of all setup menus, including audio and video functions.







Printed in U.S.A. 3/06-5M TV pictures simulated. Specifications subject to change without notice. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. RCA and associated marks are trademarks of THOMSON S.A. used under license to TTE Corporation.